



呼び名	寸法(mm)							鉄筋												参考重量 (kg)
								①		②		③		④		⑤		⑥		
	C	B	b	e	f	h'	H	径	本数	径	本数	径	本数	径	本数	径	本数	径	本数	
300	300	355	82.5	55	55	320	460	5.0	7	5.0	5	D6	8	4.0	4	D6	8	4.0	4	210
	400	355	82.5	55	55	420	560	5.0	7	5.0	7	D6	8	4.0	4	D6	8	4.0	4	239
	500	355	82.5	55	55	520	660	D6	6	6.0	6	D6	8	4.0	4	D6	8	4.0	4	267
	600	365	72.5	75	35	620	760	D6	8	6.0	7	D6	8	4.0	4	D6	8	4.0	4	317
	700	365	72.5	75	35	720	860	D6	8	6.0	8	D6	8	4.0	4	D6	8	4.0	4	349
	800	375	72.5	75	35	820	960	D10	5	D6	7	D6	8	4.0	4	D6	8	4.0	4	410
	900	375	67.5	85	25	920	1060	D10	6	D6	8	D6	8	4.0	4	D6	8	4.0	4	446
	1000	385	67.5	85	25	1020	1160	D10	6	D6	8	D6	8	4.0	4	D6	8	4.0	4	521
1100	385	67.5	85	25	1120	1260	D10	7	D6	9	D6	8	4.0	4	D6	8	4.0	4	561	

製品名	KS可変側溝
サイズ	300×300～1100×1000
荷重	T-25
栗本建材株式会社 クリモトコンクリート	